



The Bravo 2000 electric inflater consists of a main motor and a supplementary (booster) motor, which increases the capacity and pressure. The two motors can run simultaneously to obtain maximum capacity and pressure.

On the Bravo 2000, you can press the orange button to just run the main motor, or you can press the red button to switch on the booster to help obtain maximum performance. Both motors are protected by thermal fuses.

FEATURES

- Inflates and deflates
- Has a robust outer steel casing for additional protection
- Fitted with main motor and a booster motor to increase capacity and pressure
- 3m integral mains power lead comes with 2 pin plug*

- Comes with an inflation hose, 7 different adapters and a shoulder carry strap

USED FOR

- Inflation/deflation of inflatable shelters and decon showers and some water rescue products (see over)

TECHNICAL DATA

Bravo 2000 Electric Inflater

Product Code	180026
Voltage Supply	230V (Main Motor) 230V (Booster)
Plug	*Schuku (European) UK Adapter P/N: 180012/TYPE C
Max. Power	1000W / 2000W
Max. Pressure	140 mbar (2 psi) / 400 mbar (5.8 psi)
Max. Flow Rate	1200 l/min / 2000 l/min
Dimensions	32 x 17 x 26 cm
Weight	4.1 kg



COMPATIBLE WITH

- Rescue Sleds (all)
- Evacuation Raft (all)
- Animal Rescue Paths (all)
- Inflatable Decontamination Showers (all)
- Inflatable Shelters (all)
- Inflatable reservoir

NOT COMPATIBLE WITH

- ✗ Rescue Craft & Multi-Function Craft (all)
- ✗ Jet Ski Rescue Board
- ✗ Airtrack Rescue Paths (all)
- ✗ API Stretcher
- ✗ Inflatable Stretcher